

PLAN

- NOTES:
1. CONCRETE MINIMUM STRENGTH – 5,000 PSI @ 28 DAYS.
 2. STEEL REINFORCEMENT – ASTM A615, GRADE 60.
 3. MINIMUM STEEL COVER – 1-1/2 INCH TYPICAL
 4. DESIGN LOADING – AASHTO HS20-44.
 5. DESIGN SPECIFICATIONS – ACI 318 & AASHTO LOAD FACTOR DESIGN METHOD.
 6. ALL TERMINATORS SHALL HAVE BELL ENDS FLUSH WITH THE INSIDE WALL.
 7. TERMINATORS MAY BE SPECIFIED IN LIEU OF KNOCKOUTS AT THE DIRECTION OF NSTAR.
 8. CONSTRUCTION JOINT SHALL BE SEALED WITH 1"Ø BUTYL RUBBER OR APPROVED EQUAL.
 9. RACKING/STANCHIONS SOLD SEPARATELY.

SHEA *New England's Premier Precaster*
CONCRETE PRODUCTS
 800-696-7432 (SHEA)
 www.sheaconcrete.com

773 Salem Street—Wilmington, MA 153 Cranberry Hwy—Rochester, MA
 87 Haverhill Road—Amesbury, MA 160 Old Turnpike Rd—Nottingham, NH
 Mail to: PO Box 520—Wilmington, MA 01887


NSTAR UTILITY MANHOLE M1214
8'-0"W x 14'-0"L x 8'-0"H

Page: K6.12.1
 NSTAR UM 1214.dwg
 01/01/2013

NPCA
 CERTIFIED PLANNING

(24) 5/8" DIA THREADED STEEL INSERT (BOTH LONG WALLS)

3 POSITION STANCHION (TYP.)




4 POSITION STANCHION (TYP.)

SECTION A-A

OPPOSITE WALLS ARE MIRROR IMAGES.

4/0 BARE COPPER GROUND WIRE



(2) 31"x56" KNOCKOUT WINDOWS

(12) 1/4" BONDING INSERTS

1/2"Ø RECESSED NEW PI-2 (POLYPROPYLENE) PULLING IRONS (T&B)

13" SQ. X 4" DEEP SUMP

SECTION B-B

OPPOSITE WALLS ARE MIRROR IMAGES.



New England's Premier Precaster

800-696-7432 (SHEA)

www.sheaconcrete.com

NSTAR UTILITY MANHOLE M1214
8'-0"W x 14'-0"L x 8'-0"H

773 Salem Street-Wilmington, MA
87 Haverhill Road-Amesbury, MA

153 Cranberry Hwy-Rochester, MA
160 Old Turnpike Rd-Nottingham, NH

Mail to: PO Box 520-Wilmington, MA 01887

Page: K6.12.2

NSTAR UM 1214.dwg

01/01/2013

