



EXTERIOR COATING
IF REQ'D

FLAT TOP

| HEIGHT | ITEM NO | WEIGHT |
|--------|-------------|---------|
| 1'-0" | MH10-FT10ID | 16,014# |

RISER SECTION

| HEIGHT | ITEM NO | WEIGHT |
|--------|---------------|---------|
| 2'-0" | MH10-24CS10ID | 9,310# |
| 3'-0" | MH10-36CS10ID | 13,965# |
| 4'-0" | MH10-48CS10ID | 18,620# |
| 5'-0" | MH10-60CS10ID | 23,275# |
| 6'-0" | MH10-72CS10ID | 27,930# |

BASE SECTION

| HEIGHT | ITEM NO | WEIGHT |
|--------|--------------|---------|
| 3'-6" | MH10-42S10ID | 29,863# |
| 4'-6" | MH10-54S10ID | 34,518# |
| 5'-6" | MH10-66S10ID | 39,173# |

NOTES:

1. CONCRETE: 5,000 PSI MINIMUM AFTER 28 DAYS.
2. REINFORCED STEEL CONFORMS TO LATEST ASTM A185 SPEC. 0.30 SQ. IN./LINEAL FT. AND 0.30 SQ. IN. (BOTH WAYS) BASE BOTTOM.
3. H-20 DESIGN LOADING PER AASHTO HS-20-44; ASTM C478 SPEC FOR "PRECAST REINFORCED CONCRETE MANHOLE SECTIONS."
4. BUTYL RESIN SECTION JOINT CONFORMS TO LATEST ASTM C990 SPECIFICATION.
5. STEEL REINFORCED COPOLYMER POLYPROPYLENE PLASTIC STEP CONFORMS TO LATEST ASTM C478 SPEC.



New England's Premier Precaster
800-696-7432 (SHEA)
www.sheaconcrete.com

MANHOLE
120" DIA

773 Salem Street-Wilmington, MA 153 Cranberry Hwy-Rochester, MA
87 Haverhill Road-Amesbury, MA 160 Old Turnpike Rd-Nottingham, NH
Mail to: PO Box 520-Wilmington, MA 01887

Page: G6.1

manh120in.dwg 02/01/2013

