



RISER SECTION

HEIGHT	ITEM NO	WEIGHT
1'-0"	MH-12CS5ID	1,278#
2'-0"	MH-24CS5ID	2,555#
3'-0"	MH-36CS5ID	3,834#
4'-0"	MH-48CS5ID	5,112#
5'-0"	MH-60CS5ID	6,390#

BASE SECTION

HEIGHT	ITEM NO	WEIGHT
2'-6"	MH-30S5ID	5,132#
3'-6"	MH-42S5ID	6,409#
4'-6"	MH-54S5ID	7,687#
5'-6"	MH-66S5ID	8,965#

FLAT TOP

HEIGHT	ITEM NO	WEIGHT
1'-0"	MH-FT5ID	3,098#

NOTES:

1. CONCRETE: 4,000 PSI MINIMUM AFTER 28 DAYS.
2. REINFORCED STEEL CONFORMS TO LATEST ASTM A185 SPEC. 0.15 SQ. IN./LINEAL FT. AND 0.15 SQ. IN. (BOTH WAYS) BASE BOTTOM.
3. H-20 DESIGN LOADING PER AASHTO HS-20-44; ASTM C478 SPEC FOR "PRECAST REINFORCED CONCRETE MANHOLE SECTIONS."
4. BUTYL RESIN SECTION JOINT CONFORMS TO LATEST ASTM C990 SPECIFICATION.
5. STEEL REINFORCED COPOLYMER POLYPROPYLENE PLASTIC STEP CONFORMS TO LATEST ASTM C478 SPEC.



New England's Premier Precaster  
800-696-7432 (SHEA)  
www.sheaconcrete.com

MANHOLE  
60" DIA

773 Salem Street  
P.O. Box 520  
Wilmington, MA 01887

87 Haverhill Road  
P.O. Box 807  
Amesbury, MA 01913

160 Old Turnpike Road  
Nottingham, NH 03290

Page: G3.1

manh60in.dwg

1/17/2006

