



FLAT TOP

HEIGHT	ITEM NO	WEIGHT
1'-0"	MH8-FT8ID	11,225#

RISER SECTION

HEIGHT	ITEM NO	WEIGHT
2'-0"	MH8-24CS8ID	6,102#
3'-0"	MH8-36CS8ID	9,153#
4'-0"	MH8-48CS8ID	12,204#
5'-0"	MH8-60CS8ID	15,255#
6'-0"	MH8-72CS8ID	18,306#

BASE SECTION

HEIGHT	ITEM NO	WEIGHT
3'-6"	MH8-42S8ID	18,690#
4'-6"	MH8-54S8ID	21,740#
5'-6"	MH8-66S8ID	24,790#

NOTES:

1. CONCRETE: 4,000 PSI MINIMUM AFTER 28 DAYS.
2. REINFORCED STEEL CONFORMS TO LATEST ASTM A185 SPEC. 0.18 SQ. IN./LINEAL FT. AND 0.18 SQ. IN. (BOTH WAYS) BASE BOTTOM.
3. H-20 DESIGN LOADING PER AASHTO HS-20-44; ASTM C478 SPEC FOR "PRECAST REINFORCED CONCRETE MANHOLE SECTIONS."
4. BUTYL RESIN SECTION JOINT CONFORMS TO LATEST ASTM C990 SPECIFICATION.
5. STEEL REINFORCED COPOLYMER POLYPROPYLENE PLASTIC STEP CONFORMS TO LATEST ASTM C478 SPEC.



New England's Premier Precaster  
800-696-7432 (SHEA)  
www.sheaconcrete.com

MANHOLE  
96" DIA

773 Salem Street  
P.O. Box 520  
Wilmington, MA 01887

87 Haverhill Road  
P.O. Box 807  
Amesbury, MA 01913

160 Old Turnpike Road  
Nottingham, NH 03290

Page: G5

manh96in.dwg

1/17/2006

