


2" TAPER

NOTES:

1. CONCRETE: 4,000 PSI MINIMUM AFTER 28 DAYS.
2. DESIGN CONFORMS WITH 310 CMR, SECTION 15.00 DEP TITLE 5 REGS FOR SEPTIC TANKS
3. ALL REINFORCEMENT PER ASTM C1227.
4. BAFFLE WALL OPTIONAL FOR TWO COMPARTMENT TANKS.
5. OPTIONAL SLOT OPENING IN BAFFLE WALL.
6. TEES AND GAS BAFFLE SOLD SEPARATELY.
7. TONGUE & GROOVE JOINT SEALED WITH BUTYL RESIN.
8. IF COVER EXCEEDS 4 FEET, HEAVY DUTY TANK REQUIRED.  
AVAILABLE IN AASHTO HS-20 LOADING.

SHEA PRODUCT ID: M15002CWS/M15002CWSH	PREPARED FOR:	FILE NAME: tkM1500CWS.dwg	
WEIGHT (LBS): 11,641#/13,155#	DRAWN BY: ARO	DATE: 06/01/18	
773 Salem Street-Wilmington, MA   153 Cranberry Hwy-Rochester, MA   87 Haverhill Road-Amesbury, MA   160 Old Turnpike Rd-Nottingham, NH			