



NOTES:

1. CONCRETE: 5,000 PSI MINIMUM AFTER 28 DAYS.
2. DESIGN CONFORMS WITH 310 CMR 15.00, DEP TITLE 5 REGS FOR ALTERNATIVE SYSTEMS WHERE A LIQUID LEVEL OF FOUR FEET IS NOT FEASIBLE.
3. ALL REINFORCEMENT PER ASTM C1227.
4. DESIGNED FOR AASHTO HS-20 LOADING, COVER 1-5 FT.
5. TONGUE AND GROOVE JOINT SEALED WITH BUTYL RESIN. INLET HEIGHT MAY INCREASE SLIGHTLY DUE TO THE BUTYL RESIN USED.
6. TEES AND BAFFLES SOLD SEPARATELY.

SINGLE COMPARTMENT TANK										
GALLONS	A (HEIGHT)	B (INLET) 6" BOOT	B (INLET) 4" BOOT	C (LIQUID)	WEIGHT (LBS)	ITEM NO.	SIZE TOP	WEIGHT TOP	SIZE BOTTOM	WEIGHT BOTTOM
2,500	62"	46"	47"	37"	40,749	8x17-25	28"	20,720"	34"	20,029
3,000	69"	53"	54"	44"	43,166	8x17-30	35"	23,137	34"	20,029