


BUILDINGS USED FOR:
 RESTROOMS
 STORAGE
 HAZMAT
 PUMP SYSTEMS
 COMMUNICATIONS
 DUGOUTS
 CONCESSIONS
 ETC...

Notes:

1. Concrete strength $f'c=5,000$ psi min.
2. Steel reinforcement yield strength $F_y=60,000$ psi min.
3. All openings for electric, mechanical, louvers, etc. sized as required.
4. Standard Finishes (custom finishes available):
 Exterior: Broom, Brick, Exposed Aggregate, Split Block, Barnboard.
 Interior: Concrete, FRP
5. Standard Dimensions:
 Exterior: 10' x 12', 12' x 16' 12' x 20'; custom sizes available.
 Interior Heights: 8'; custom heights available.
6. Standard double doors, 6' x 6'-8" x 13/4"; 18-gauge galvanized steel;
7. Two 12.5-gauge screened aluminum vents; minimum 7" x 18".
8. Post-tensioned roof and floor.
9. Exclusive turn-down roof with built-in drip edge.
10. Roof load capacity: 60 psf standard; higher loadings available.
11. Wind load: 130 mph standard; higher loadings available.
12. Rated Seismic Zone 4.
13. Bullet tested to UL 752, Level 4 (30 caliber rifle fired at 15 feet).
14. Floor load: 250 psf standard; additional capacities available.
15. For larger sizes Easi-Span Building Standard Dimensions:
 Clear-span widths: 20', 24', 30' and 40'.
 Lengths: up to 200' in multiples of 10'.
 Interior Heights: 9'; custom heights available

SHEA PRODUCT ID:	PREPARED FOR:	FILE NAME: Easi-Set Building.dwg	
WEIGHT (LBS):	DRAWN BY: ARO	DATE: 03/01/2018	